

LS Tractor
Start Blue. Stay Blue.

THE NEW & IMPROVED
MT4 SERIES



AVAILABLE IN ROPS & CAB

DESIGN



MT4 CAB DESIGN

- With the new cabin design, we increase interior space by over 15%

ALL NEW HOOD DESIGN (LS FAMILY LOOK)

- Redesigned hood allows for full opening and improved engine serviceability
- New 73HP ROPS model

UPGRADED

- Handle design enhancement
- Knob design enhancement
- Switch (PTO, Combi) enhancement
- Enhanced grip and ease of operation

LED HEADLAMP FOR ENTIRE LINEUP

- Improved visibility with rear LED lamp installation



4 DIFFERENT TIRE OPTIONS

- Standard Ag 9.5 - 24 / 16.9 - 28
- IND 10.5/80x18 10PR / 19.5Lx24 8PR
- Large Ag 11.2-24 / 16.9-30 (Recommended for 73 HP)
- R14 320/85R20 119D / 420/75R34 142D

NEW COLOR MATCH

- Deep sky blue & silver rim



CONVENIENCE



- Improved high back seat with wider and improved cushion comfort
- Sharp LS logo imprint on seat
- Standard improved armrests



- Wraparound style exterior and interior for improved visibility
- Optimized control layout for user convenience



- Standard TF-LCD instrument panel shows regen time, oil change intervals, etc



- New multi-use side console



- Installed indoor handrail



- Standard 3rd function button on joystick

OPTIMIZATION

- Weight balance optimization
 - Weight increased by 400 lb. to enhance tractor stability and operations
- Engine frame & front axle reinforcement
- Larger size tire is available (16.9-30)
- Upgraded oil flow and front loader lift capacity
 - 14.5 g/m (implement) / 6.6 g/m (steering)
 - One of the best loader lift capacities in its class at up to 3,487 lb.
- Standard self leveling loader
- Optional shockless accumulator



- Relocated the muffler to improve visibility
- Expanded front glass to improve visibility



- Sectional type remote valve
- 2 pairs are standard (additional pair optional)



NEW MT4 SERIES SPECIFICATIONS

Model	MT463	MT463PS	MT463C	MT463CPS	MT473	MT473PS	MT473C	MT473CPS
ENGINE								
Type	Vertical Water-Cooled 4Cycle Diesel Engine							
Model (Tier4)	L4C25-T							
Engine HP (gross)	63				73			
PTO HP	54.1				62.9			
Rated Speed, rpm	2,500							
Displacement (in ³)	152.85							
Fuel Tank Capacity (gal.) (L)	24.3 (92)							
DRIVE TRAIN								
Transmission	Synchro Shuttle	Electro Power Shuttle	Synchro Shuttle	Electro Power Shuttle	Synchro Shuttle	Electro Power Shuttle	Synchro Shuttle	Power Shuttle
No. Of Speed	F16 x R16							
Brakes	Wet, Multi-disc							
PTO								
Type	Independent							
Rear (rpm)	540, 540E (Std.)							
HYDRAULIC SYSTEM								
Control System	Position / Draft							
Implement Pump (gpm)	14.5							
Steering Pump (gpm)	6.6							
Total Flow (gpm)	21.1							
Category (3pt Hitch)	CAT II							
Hitch Lift Capacity (@610mm, lbs.)	3,483 (@ 24" From The Hitch End)							
Remote Valves	2 Pairs (Front), 2 Pairs (Rear)							
Steering	Hydrostatic Power Steering							
DIMENSION								
Overall length, Bumper To Link (in.)	140							
Overall Width, Tires (in.)	72.6							
Wheelbase (in.)	83.1							
Height To Top Of ROPS/Cab (in.)	113.9		105.4		113.9		105.4	
TIRE SIZE								
Standard Ag Front / Rear	9.5 - 24 / 16.9 - 28							
IND Front / Rear	10.5/80x18 10PR / 19.5Lx24 8PR							
Large Ag Front / Rear	11.2-24 / 16.9-30							
R14 Front / Rear	320/85R20 119D / 420/75R34 142D							
WEIGHT								
Total Weight (W/O Ballast) (lbs.)	5,313		5,776		5,423		5,886	

FRONT END LOADER	LL5001	
TRACTOR APPLICATION	NEW MT4	
	HEIGHT POSITION	POWER POSITION
Bucket Size (in.)	78	
Maximum Lift Height (in.)	132.9	116.8
Lift Capacity (At Pivot Pin, Max. Height) (lbs.)	3,426	3,488
Maximum Dump Angle (deg.)	44.4	59.7
Bucket Capacity (gal.)	126.8	126.8
Bucket Rollback Force (At Ground Level) (lbs.)	3,524	3,529
Digging Depth (in.)	6	5.1
Loader Weight (W/O Bucket) (lbs.)	1,190	



LS Tractor

LS Tractor USA | P: 252.984.0700
 F: 252.984.0701 | LSTractorUSA.com
 (Corporate Address) 6900 Corporation
 Parkway, Battleboro, NC

Note: Specifications and design are subject to change without prior notice.